



EBCD 68



combined distribution and outlet box

Properties alignable, with coupling system for aligning in standard distance of 71 mm and adjustable fixing of outlet devices, mounting screw spacing 60 mm

Colour black, similar to RAL 9005

Standard: ÖVE/ÖNORM EN 60670-1:2014, ÖVE/ÖNORM EN 60670-22:2007



Halogen free
True

Degree of protection (IP)
IP20

| Art. no. | Part No. | Dimensions | VPE (pc) small/medium/large |
|----------|---|--------------|-----------------------------|
| 102 192 | EBCD 68 100 pc. bag | Ø 75 x 45 mm | 1 / 7 / 42 |
| 102 193 | EBCD 68 25 pc. bag | Ø 75 x 45 mm | - / 4 / 140 |
| 102 194 | EBCD 68 20 pc. bag | Ø 75 x 45 mm | 1 / 5 / 175 |
| 102 191 | EBCD 68 100 pc. box individually labelled | Ø 75 x 45 mm | - / 100 / 3500 |
| 102 195 | EBCD 68 Plus 50 pc. box individually labelled | Ø 75 x 65 mm | - / 50 / 1750 |
| 105 124 | EBCD 68 Plus 25 pc. bag | Ø 75 x 65 mm | 1 / 4 / 96 |

Areas of Recommended Application

| | |
|------------------------------|----------|
| break-out opening | True |
| seal membrane | False |
| nozzle | False |
| step membrane | False |
| Mounting switching equipment | Screwing |
| Luminaire hook mounting | False |
| Nozzle | None |
| With nail lugs | False |
| Circuit integrity | None |

Further technical details

| | |
|------------------------------|-------------------------|
| Model | Single |
| Shape | Round |
| Mounting method | Flush mounted (plaster) |
| With screws | False |
| Provided with revolving ring | |
| Connectable | True |
| Equipped with | None |
| Cover attachment | Snap on |
| Material | PS |