

EBHD 68



outlet box, single gang

Properties	mounting screw spacing 60 mm, drilled hole size required Ø 68 mm, box rim diameter Ø 71 mm, for partition board thickness from 7 to 35 mm, maximum 4 conduit entries Ø 20 mm, 2 conduit entries Ø 25 mm and 4 cable entries
Colour	orange, similar to RAL 2004
Usage	for dry lining installations

Standard: ÖVE/ÖNORM EN 60670-22:2007



Halogen free
False

Degree of protection (IP)
IP30

Art. no.	Part No.	Dimensions	VPE (pc) small/medium/large
102 229	EBHD 68 200 pc. box individually labelled	Ø 65 x 45 mm	- / 200 / 4800
102 230	EBHD 68 20 pc. bag	Ø 65 x 45 mm	1 / 24 / 216
102 232	EBHD 68 Plus 150 pc. box individually labelled	Ø 65 x 60 mm	- / 150 / 3600
102 233	EBHD 68 Plus 20 pc. bag	Ø 65 x 60 mm	1 / 10 / 180

Areas of Recommended Application

break-out opening	True
seal membrane	False
nozzle	False
step membrane	False
Mounting switching equipment	Screwing
Luminaire hook mounting	False
Nozzle	None
With nail lugs	False
Circuit integrity	None

Further technical details

Model	Single
Shape	Round
Mounting method	Hollow wall
With screws	True
Provided with revolving ring	
Connectable	
Equipped with	None
Cover attachment	Screwed
Material	PP-Blend