



## EBMS LG



saddle, with two fixing holes

### Properties

for mounting of rigid or pliable conduits with screws  $\varnothing$  4 mm

### Colour

light grey, similar to RAL 7035



### Working temperature

-5 to +60 °C

Art. no.	Part No.	For tube diameter	VPE (pc) small/medium/large
101 370	EBMS 16 lg/5 pc. bag	16 mm	1 / 360 / 8640
101 371	EBMS 16 lg/20 pc. bag	16 mm	1 / 130 / 3120
101 525	EBMS 16 lg/50 pc. box	16 mm	1 / 32 / 768
101 372	EBMS 20 lg/5 pc. bag	20 mm	1 / 320 / 7680
101 373	EBMS 20 lg/10 pc. bag	20 mm	1 / 160 / 3840
101 526	EBMS 20 lg/50 pc. box	20 mm	1 / 24 / 576
101 374	EBMS 25 lg/5 pc. bag	25 mm	1 / 220 / 5280
101 527	EBMS 25 lg/50 pc. box	25 mm	1 / 16 / 384
101 375	EBMS 32 lg/5 pc. bag	32 mm	1 / 100 / 2400
101 528	EBMS 32 lg/50 pc. box	32 mm	1 / 12 / 288
101 376	EBMS 40 lg/5 pc. bag	40 mm	1 / 60 / 1440
101 542	EBMS 40 lg/400 pc. box individually labelled	40 mm	- / 400 / 9600
101 543	EBMS 50 lg/400 pc. box individually labelled	50 mm	- / 400 / 9600

### Further technical details

Closed	True
Tackable	False
Max. number of tubes	1
Type of fastening	Screw hole
With inlay	False
Material	PVC