



EBPQ



distribution box

Properties	with pre-punched conduit entries, easy to knock-out
Colour	black, similar to RAL 9005
Classification	AC 400 V

Standard: ÖVE/ÖNORM EN 60670-1:2014, ÖVE/ÖNORM EN 60670-22:2007



Halogen free
True

Degree of protection (IP)
IP30

Art. no.	Part No.	Dimensions	VPE (pc) small/medium/large
106 663	EBPQ 75 160 pc. box individually labelled	75 x 75 x 50 mm	- / 160 / 5600
106 664	EBPQ 75 50 pc. box individually labelled	75 x 75 x 50 mm	- / 50 / 5600
106 665	EBPQ 75 QD 20 pc. bag	75 x 75 x 50 mm	1 / 9 / 180
106 666	EBPQ 100 140 pc. box individually labelled	100 x 100 x 50 mm	- / 140 / 3360
106 667	EBPQ 100 50 pc. box individually labelled	100 x 100 x 50 mm	- / 50 / 3900
106 668	EBPQ 100 QD 20 pc. bag	100 x 100 x 50 mm	1 / 6 / 120
106 669	EBPQ 150 100 pc. box individually labelled	150 x 150 x 70 mm	- / 100 / 1800
106 670	EBPQ 150 40 pc. box individually labelled	150 x 150 x 70 mm	- / 40 / 1400
106 671	EBPQ 200 40 pc. box individually labelled	200 x 200 x 80 mm	- / 40 / 720
106 672	EBPQ 200 20 pc. box individually labelled	200 x 200 x 80 mm	- / 20 / 480

Areas of Recommended Application

break-out opening	True
seal membrane	False
nozzle	False
step membrane	False
Mounting switching equipment	
Luminaire hook mounting	False
Nozzle	None
With nail lugs	False
Circuit integrity	None

Further technical details

Model	Single
Shape	Square
Mounting method	Flush mounted (plaster)
With screws	False
Provided with revolving ring	False
Connectable	False
Equipped with	None
Cover attachment	Screwed
Material	PS