

combined distribution and outlet box



alignable, with coupling system for aligning in standard distance of 71 mm and adjustable fixing of outlet devices, mounting screw spacing 60 mm

Colour black, similar to RAL 9005

Standard: ÖVE/ÖNORM EN 60670-1:2014, ÖVE/ÖNORM EN 60670-22:2007



Halogen free

False

Degree of protection (IP)

IP20

Art. no.	Part No.	Dimensions	VPE (pc) small/medium/large
102 200	EBS D 68/2 50 pc. box individually labelled	143 x 70 x 41 mm	- / 50 / 1750
102 201	EBS D 68/2 10 pc. bag	143 x 70 x 41 mm	1 / 5 / 175
102 202	EBS D 68/3 50 pc. box individually labelled	212 x 70 x 41 mm	- / 50 / 1200

Areas of Recommended Application

break-out opening	True
seal membrane	False
nozzle	False
step membrane	False
Mounting switching equipment	Screw or spread out
Luminaire hook mounting	False
Nozzle	None
With nail lugs	False
Circuit integrity	None

Further technical details

Model	Double
Shape	Oval
Mounting method	Flush mounted (plaster)
With screws	False
Provided with revolving ring	False
Connectable	True
Equipped with	None
Cover attachment	Snap on
Material	PS