



## grip type coupler, halogen-free

<b>Properties</b>	for waterproof and tight connection of pliable conduits especially for use in concrete installation, protection type IP65, extraction resistance 250 N
<b>Colour</b>	grey, similar to RAL 7037
<b>Fire Behaviour</b>	non flame propagating

**Standard:** ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-22:2012



Art. no.	Part No.	For tube diameter	VPE (pc) small/medium/large
103 681	EBVK 16 gr/10 pc. bag	16 mm	1 / 120 / 2880
103 683	EBVK 16 gr/50 pc. box	16 mm	1 / 24 / 576
103 684	EBVK 16 gr/50 pc. box individually labelled	16 mm	50 / 1200 / 28800
101 368	EBVK 20 gr/10 pc. bag	20 mm	1 / 80 / 1920
101 521	EBVK 20 gr/50 pc. box	20 mm	1 / 16 / 384
103 195	EBVK 20 gr/100 pc. box	20 mm	1 / 8 / 192
101 523	EBVK 20 gr/100 pc. box individually labelled	20 mm	100 / 800 / 19200
101 369	EBVK 25 gr/10 pc. bag	25 mm	1 / 60 / 1440
101 522	EBVK 25 gr/50 pc. box	25 mm	1 / 12 / 288
101 524	EBVK 25 gr/50 pc. box individually labelled	25 mm	50 / 600 / 14400
103 196	EBVK 32 gr/25 pc. box individually labelled	32 mm	25 / 300 / 7200
103 197	EBVK 40 gr/25 pc. box individually labelled	40 mm	25 / 200 / 4800
103 307	EBVK 50 gr/15 pc. box individually labelled	50 mm	15 / 120 / 2880

### Further technical details

Halogen free	False
Model	Extraction proof
Material	PE