



EBXL LG



pliable insulation conduit, corrugated

Properties	light compression resistance, light impact resistance
Colour	light grey, similar to RAL 7035
Fire Behaviour	non flame propagating
Classification	22212

Standard: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-22:2012



Compressive strength class Light (Class 2)		Impact strength Light (Class 2)	Operating temperature -5 to +60 °C	Bending strength Flexible
Art. no.	Part No.	Outer diameter	Inner diameter	VPE (pc) small/medium/large
101 624	EBXL 16 lg 10 m	16 mm	12,1 mm	1 / - / 180
101 625	EBXL 16 lg 25 m	16 mm	12,1 mm	1 / - / 60
100 499	EBXL 16 lg 50 m	16 mm	12,1 mm	1 / - / 54
101 626	EBXL 20 lg 10 m	20 mm	15 mm	1 / - / 180
101 627	EBXL 20 lg 25 m	20 mm	15 mm	1 / - / 90
100 500	EBXL 20 lg 50 m	20 mm	15 mm	1 / - / 54
107 046	EBXL 20 lg 100 m	20 mm	15 mm	1 / - / 40
101 628	EBXL 25 lg 10 m	25 mm	19,1 mm	1 / - / 144
101 629	EBXL 25 lg 25 m	25 mm	19,1 mm	1 / - / 60
100 501	EBXL 25 lg 50 m	25 mm	19,1 mm	1 / - / 32
107 047	EBXL 25 lg 100 m	25 mm	19,1 mm	1 / - / 14
101 630	EBXL 32 lg 10 m	32 mm	23,7 mm	1 / - / 50
100 502	EBXL 32 lg 25 m	32 mm	23,7 mm	1 / - / 27
100 504	EBXL 40 lg 25 m	40 mm	31,2 mm	1 / - / 20
100 505	EBXL 50 lg 25 m	50 mm	39,6 mm	1 / - / 12

Areas of Recommended Application

Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	False
Machine and systems installation	False
Suitable for subsurface installation (screed))	False
Outdoor installation	False
Suitable for installation on wood	False
Hollow wall	False
Underground installation	False

Further technical details

Halogen free	False
High conducting inner coating	False
With sleeve	False
Fire retardant version	True
Material	PVC-U