



EBXM GR



pliable conduit, corrugated

Properties	medium compression resistance, medium impact resistance
Colour	grey, similar to RAL 7037
Fire Behaviour	non flame propagating
Classification	33412

Standard: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-22:2012



Compressive strength class Medium (class 3)	Impact strength Medium (class 3)	Operating temperature -25 to +60 °C	Bending strength Flexible
---	--	---	-------------------------------------

Art. no.	Part No.	Outer diameter	Inner diameter	VPE (pc) small/medium/large
101 631	EBXM 16 gr 10 m	16 mm	10 mm	1 / - / 180
101 632	EBXM 16 gr 25 m	16 mm	10 mm	1 / - / 60
100 506	EBXM 16 gr 50 m	16 mm	10 mm	1 / - / 54
101 633	EBXM 20 gr 10 m	20 mm	13,6 mm	1 / - / 180
101 634	EBXM 20 gr 25 m	20 mm	13,6 mm	1 / - / 90
100 507	EBXM 20 gr 50 m	20 mm	13,6 mm	1 / - / 54
107 048	EBXM 20 gr 100 m	20 mm	13,6 mm	1 / - / 40
101 635	EBXM 25 gr 10 m	25 mm	18 mm	1 / - / 144
101 636	EBXM 25 gr 25 m	25 mm	18 mm	1 / - / 60
100 508	EBXM 25 gr 50 m	25 mm	18 mm	1 / - / 32
107 049	EBXM 25 gr 100 m	25 mm	18 mm	1 / - / 14
101 637	EBXM 32 gr 10 m	32 mm	23,7 mm	1 / - / 50
100 509	EBXM 32 gr 25 m	32 mm	23,7 mm	1 / - / 27
100 510	EBXM 40 gr 25 m	40 mm	31,2 mm	1 / - / 20
100 511	EBXM 50 gr 25 m	50 mm	39,6 mm	1 / - / 12

Areas of Recommended Application

Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	True
Machine and systems installation	True
Suitable for subsurface installation (screed))	True
Outdoor installation	False
Suitable for installation on wood	True
Hollow wall	True
Underground installation	True

Further technical details

Halogen free	False
High conducting inner coating	True
With sleeve	False
Fire retardant version	True
Material	PVC-U